

ECORE™ Advanced Wall Technology digital base specifications

Specifications	Smooth	Silk	Dapple
SKU# for 10 yard roll	EC14-10	EC04-10	EC02-10
SKU# for 50 yard roll	EC14-50	EC04-50	EC02-50
SKU# for 300 yard roll	EC14-300	EC04-300	EC02-300
Performane Level:	Type II	Type II	Type II
Printable Width:	54"	54"	54"
Finished Total Weight:	9.0 oz./lin. yd. 6.0 oz./sq. yd.	9.0 oz./lin. yd. 6.0 oz./sq. yd.	9.0 oz./lin. yd. 6.0 oz./sq. yd.
Backing:	N/A	N/A	N/A
Tensile Breaking Strength:	75 x 75 lbs.	75 x 75 lbs.	75 x 75 lbs.
Tear Strength (Scale Reading):	147 x 129	147 x 129	147 x 129

Specifications:

Class A. Meets or exceeds G.S.A. Federal Specifications CCC-W-408D for Type II material.

Fire Classification:

The base product carries a NFPA and IBC Class A interior wall and finish rating when tested using the ASTM E-84 method on reinforced cement board and Type X gypsum board and when tested in accordance with NFPA 286. Subsequent coating, printing or other alteration may adversely affect such fire ratings.

Product Features:

- Non-PVC construction
- Breathable
- Recyclable through OMNOVA Reclamation Program
- Low VOC emitting
- Durable with long life cycle
- Digital-ready base products are provided with a 5-year limited warranty subject to certain conditions and limitations. For complete warranty terms, go to: www.omnova.com/viewnique/viewnique.aspx.

