

Silken



with  $\ensuremath{\text{PreFixe}}^{\ensuremath{\text{refixe}}}$  protective finish



## Silken

## **TYPICAL PROPERTIES**

Content	100% vinyl face, polyester knit backing
Finish	PreFixx <sup>®</sup> Protective Finish
Width	54 in. [137 cm]
Roll Size	40 lin yd [37 lin m]
Weight	30 oz/lin yd. [929 g/lin m]

VL

2

## PERFORMANCE REQUIREMENTS

Abrasion Resistance (CFFA-1a) - cycles - Wyzenbeek stainless steel wire screen	60,000
- Cotton duck abradant	400,000
Mildew Resistance (ASTM G-21)	Pass
Cold Crack - °F	-20
U.V. Resistance (CFFA-2) - Hours outdoor	650
Flame Retardant Rating	
- BIFMA, Class A	Pass
- Cal. Technical Bulletin 117-2013, Section 1	Pass
- Cal. Technical bulletin 117-2015, Section 1	1 455
- NFPA 260, Class 1	Pass

Upholstery protected with **PreFixx** protective finish is engineered to be cleaned again and again without showing signs of wear. With easy cleanability, and proven stain resistance, even the toughest stains can be wiped away without harming the upholstery when the recommended cleaning process is followed.



Though our upholstery can be used in many applications, customers are responsible for selecting an upholstery with attributes that meet the requirements of the specific end-use application – not all upholstery is suitable for all applications.

Nautolex® products are easily cleaned. For specific cleaning instructions, see downloads at www.omnova.com/nautolex



 World Headquarters

 25435 Harvard Road

 Beachwood, OH 44122

 United States

 PHONE
 +1 216 682-7000

 Fax
 +1 216 453-0104

ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM ACT Performance Guidelines icons are registered certification marks owned by the Association for Contract Textiles, Inc. NAUTOLEX and PREFIXX are registered trademarks of OMNOVA Solutions Inc. Designed and manufactured by OMNOVA Solutions Inc. © 2018 OMNOVA Solutions Inc. DTC Dec 2018